

RV Air-Conditioning Systems



Webasto RV Air Conditioners are the most effective units on the market. With many outstanding features including exceptional cooling capacity, low noise and a stylish low profile streamline design. Made using UV stabilised polypropylene the units are robust, yet still lightweight. They are the perfect investment to combat the harsh Australian climate.

Complete with an easy to handle remote control that lets you choose between heating, cooling, dry, sleep and timing functions. These functions allow your air-conditioning system to operate effectively in temperatures as low as -5°C and as high as 50°C.

Webasto Air Conditioners have excellent reverse cycle performance and are supplied with a 2 year Australia wide warranty and on-going technical support.

Features and Benefits

- 220-240 V
- Cooling Capacity from 2400 W up to 3400 W
- Low profile, slimline design
- Low noise
- High quality compressor and components
- Operates in temperatures as low as -5°C and as high as 50°C.
- Remote control to select heating, cooling, dry, sleep and timing functions
- Reverse cycle air-conditioner with a three speed fan
- Patented spiral retractable duct for easy installation
- Easy to remove & clean Air filter
- Strong and lightweight UV stabilised cover designed to withstand the toughest conditions
- 2 year Australia wide warranty

RV Air-Conditioning System



Technical Specifications

	Cool Top Trail 24	Cool Top Trail 34
Nominal Voltage (V) / Frequency (Hz)	220-240 / 50	220 - 240 / 50
Rating Cooling (kW)	2.4	3.4
Rated Heating (kW)	2.4	3.0
Rated Current Cooling / Heating / Max (A)	4.2 / 3.8 / 4.5	5.8 / 5.4 / 7.4
Unit Net Weight Outdoor (kg)	29	45
Unit Net Weight Indoor (kg)	3	3
Operating Temperature Range (°C)	-5 to 50	-5 to 50
Roof Thickness (mm)	25 to 85	25 to 70
Rooftop Cut-out (mm) - (Optional)	360 x 360 - (400 x 400)	360 x 360 - (400 x 400)
Dimensions Outdoor (L x W x H mm)	1002 x 566 x 215	1122 x 850 x 223
Dimensions Indoor (L x W x H mm)	557 x 536 x 43	575 x 556 x 49